

## Polyethylene/PVC Flange Adaptor



### Sizes Available:

63mm	c/w	50mm	PN16	Flange
90mm	c/w	80mm	PN16	Flange
110mm	c/w	100mm	PN16	Flange
125mm	c/w	100mm	PN16	Flange
140mm	c/w	150mm	PN16	Flange
160mm	c/w	150mm	PN16	Flange
180mm	c/w	150mm	PN16	Flange
200mm	c/w	200mm	PN16	Flange
225mm	c/w	200mm	PN16	Flange
250mm	c/w	250mm	PN16	Flange
280mm	c/w	250mm	PN16	Flange
315mm	c/w	300mm	PN16	Flange

- ✓ Leakproof and mechanical locking.
- ✓ Mechanical locking by a grip ring in order to avoid pipe's axial movement.
- ✓ Independent clamping.
- ✓ Wide range of diameters covering pipes from 63 to 315 millimeters.
- ✓ Suitable for PVC and polyethylene pressure pipes.
- ✓ PN-16 operating pressure.
- ✓ GGG-50 nodular cast iron.
- ✓ 250 $\mu$  EPOXY average coating.
- ✓ Equipped with DACROMET coated bolts, nuts and washers, and EPDM rubber seals.
- ✓ Grip ring made of steel.

Windmill View,  
Blackchurch,  
Rathcoole,  
Co. Dublin.

Ph. +353 (0)1 257 0388  
Fax. +353 (0)1 257 0389  
Email. sales@proflo.ie