

Universal Flange Adaptor

Nominal Size.	Range	Size of Flange
50mm	59mm To 72mm	50mm PN16
65/80mm	72mm To 85mm	65mm PN16
80mm	72mm To 85mm	80mm PN16
80mm	88mm To 103mm	80mm PN16
100mm	109mm To 128mm	100mm PN16
125mm	132mm To 146mm	150mm PN16
125mm	138mm To 153mm	150mm PN16
150mm	159mm To 182mm	150mm PN16
175mm	192mm To 210mm	200mm PN16
200mm	218mm To 235mm	200mm PN16
200mm	230mm To 247mm	250mm PN16
225mm	250mm To 267mm	250mm PN16
250mm	272mm To 289mm	250mm PN16
300mm	315mm To 332mm	300mm PN16
300mm	322mm To 339mm	300mm PN16
300mm	332mm To 349mm	300mm PN16
350mm	374mm To 391mm	350mm PN16
400mm	417mm To 437mm	400mm PN16
450mm	480mm To 500mm	450mm PN16
500mm	523mm To 546mm	500mm PN16
600mm	630mm To 650mm	600mm PN16

Body and End Flange: Ductile Iron.
Gasket: EPDM.
Coating: Blue or Black Fusion Bonded Epoxy Coated.
Nuts: To BS EN ISO 898-1
Bolts: To BS EN 4190
Washers: Stainless Steel.



Windmill View,
 Blackchurch,
 Rathcoole,
 Co. Dublin.
 Ph. +353 (0)1 257 0388
 Fax. +353 (0)1 257 0389
 Email. sales@proflo.ie