

Wrap around Saddle with Flanged Outlet

FOR COLD WATER

Flange DN	110	Pipe Ø mm			
		160	180	200	250
80	•	•	•	•	•
100		•	•	•	

For PE-pipes according to EN 1555/EN 13244
and PVC-pipes according to EN 1452
Flanged outlet - EN 1092-2

PN 10 (SDR 11) and PN 16 (SDR 7.4)
PN 10 (SDR 21) and PN 16 (SDR 13.5)

DESIGN FEATURES

- Solid construction of ductile iron epoxy powder coated
- Bolts, nuts and washers of stainless steel
- The drilled hole is sealed by an O ring inserted in the upper part saddle
- The rubber linings are bonded to the lower part of the saddle - this ensures positive positioning of saddle.

MATERIAL

Saddle body:

of ductile iron EN-GJS-400-18 according to EN 1563 (GGG 400 - DIN 1693) epoxy powder coated

Rubber in the lower part:

Elastomer (Suitable for Potable Water)

O ring seal-in the bonnet:

Elastomer, (suitable for potable water)

Bolts, Nuts and Washers:

stainless steel - A2

Pipe Ø mm	Flange DN	d Ø	H	L	L1	Weight kg
110	80	80	150	189	200	10.60
160	80	80	176	239	250	14.80
	100	100	176	239	250	14.80
200	80	80	191	270	220	16.40
	100	100	191	270	220	17.30
250	80	80	221	347	220	14.7



Windmill View,
Blackchurch,
Rathcoole,
Co. Dublin.
Ph. +353 (0)1 257 0388
Fax. +353 (0)1 257 0389
Email. sales@proflo.ie

